



ECHO CLASSIC VINYL SILK

• DESCRIPTION & FIELD OF APPLICATION

A high quality co-polymer emulsion paint with a fashionable silky decorative finish, which is extremely tough and washable for a long lasting, and luxurious sheen coating.

Echo classic vinyl silk is recommended for use on all types of interior surfaces such as concrete, cement plaster, wall papers, and pre-cast gypsum, where easy-cleaning properties are required including kitchens and bathrooms.

• MAIN FEATURES

- Good scrub resistance and highly washable
- luxurious silky sheen finish
- Long-lasting colors
- Good hiding power
- Durable
- Anti-fungus
- Fast drying
- Easy to apply
- No Lead or Mercury added
- Environmentally friendly

• PHYSICAL SPECIFICATIONS

- | | |
|------------------------|--|
| - Specific gravity | - Approx. 1.14 g/cc |
| - Volume Solids | - Approx. 24% |
| - Coverage rate | - 10-12 M ² /Liter |
| - Dry film thickness | - 30 Microns |
| - Flash point | - Not applicable |
| - Finish | - Silk |
| - Drying time at 25° C | - Surface dry approx. 1 hour
Hard dry approx. 2 hours |

* A second coat can be applied after two hours.

• SURFACE PREPARATION

The surface should be sound, dry and clean, free from dirt, oil, grease and loose paint or powdery materials.

A. OLD PAINTED SURFACES

1. Remove the old paint as much as possible.
2. Sand the entire surface and remove all the dust.
3. Wash down with Ammonia Water Solution.
4. Rinse with clean water and allow drying.
5. Prime the surface to be painted with Echo Latex Sealer.
6. Fill cracks and holes with Echo Interior putty or Echo Acrylic Filler.
7. After drying, sand the putty and clean the surface once again.
8. Apply two coats of Classic Vinyl Silk.

B. NEW SURFACES

1. Sand the surface until completely smooth, and remove all the dust.
2. Prime the surface to be painted with Echo Latex Sealer.
3. Apply 1-2 coats of Echo Interior putty or Echo Acrylic Filler.
4. After drying, sand the putty and clean the surface.
5. Apply two coats of Classic Vinyl Silk.

• **INSTRUCTIONS FOR APPLICATION**

1. **Airless spray gun**

Type of thinner	: Clean Water
Percentage of thinning	: 10 - 15% max. By volume
Nozzle orifice	: 0.371mm-0.457mm
Output pressure	: 120 - 140 bars

2. **Air spray gun**

Type of thinner	: Clean Water
Percentage of thinning	: 10 - 15% max. By volume
Nozzle orifice	: 1.5 - 2.0 mm
Output pressure	: 2 - 3 bars

3. **Brush / Roller**

Type of thinner	: Clean Water
Percentage of thinning	: 10 - 20% max. By volume

• **COLORS**

- White and light shade colors.

• **PACKING**

- 19 Ltr. Pail, 1 US gallon



- **STORAGE**

- The product must be kept in cool well-ventilated place, protected from sunlight and heat.
- Containers must be kept tightly closed after partial usage.
- Storage life: up to 5 years from date of production, if stored as suggested.

- **REMARKS**

- Stir well before use.
- Avoid application below 5° C or over 85% relative humidity.
- After painting, clean the application tools immediately with water.
- Keep out of children's reach.
- For more information, please do not hesitate to contact our Technical Department.