

ECHO WATERSEAL

(Water Repellent For stone , Marble)

• **DESCRIPTION AND RECOMMENDED USE**

Is a colorless special element liquid based on highly modified co-polymer resin and silicon which imparts permanent water repellent effects to stone and porous surfaces. It is used to prevent leakage from bricks, stone, concrete, mud walls, waterproofing of textured coatings, and decorative finishes.

• **MAIN FEATURES**

- Outstanding water repellent
- Colorless (does not alter the natural finish of the buildings)
- Excellent breathing properties
- Long lasting protections
- High penetration
- Prevents dampening of walls due to water exposure
- Excellent resistance to fungus and mildew

• **PHYSICAL SPECIFICATIONS**

- | | |
|----------------------|--|
| - Color | - clear |
| - Specific gravity | - approx 1.15 |
| - Volume Solids | - approx 40% |
| - Coverage Rate | - 10-12 m ² / Liter (depend on the surface condition) |
| - Dry Film Thickness | - 30 Microns |
| - Water resistance | - Excellent |
| - Flash point | - Not applicable |
| - Drying time | - Surface dry : 1 hour
Full dry : 3 hours |

• **SURFACE PREPARATION**

The surface must be treated by removing all forms of protrusions to get a suitable surface for application.

• **APPLICATION GUIDE**

1. The surface must be free from dust, grease, oil, and other contaminants.
2. Surface temperature during application must not be less than 10°C; the surface moisture should not exceed 8% and the relative humidity at work place not to exceed 70%.

3. Do not apply on surfaces until completely dry.
4. Adequate ventilation should be provided during drying time.
5. Apply one coat of Echo water seal, recoating is not required

- **INSTRUCTIONS FOR APPLICATION**

- Tools : Spray gun - Roller - Brush
- Thinner: No thinner is needed

- **PACKING**

- 20 liter -10 liter - 5 liter

- **STORAGE**

- The product must be kept in cool well-ventilated place, protected from sunlight and heat.
- Containers must be kept tightly closed after partial usage.
- Storage life: up to 5 years from date of production, if stored as suggested.

- **REMARKS**

- Stir well before use.
- Contact of liquid paint with eyes and skin, inhalation of paint mist and solvent vapor should be strongly avoided.
- Avoid application below 5° C or over 85% relative humidity.
- Keep out of children's reach.
- For more information, please do not hesitate to contact our Technical Department.