

ECHO-SINTEX

• DESCRIPTION & FIELD OF APPLICATION

Echo sintex is a premium quality high build textured finish based on acrylic polymer and special hard aggregates. It is intended for use on interior and exterior walls, ceilings, masonry, pre-cast concrete panels, and gypsum boards which yields a beautiful rough textured finish.

• MAIN FEATURES

- High film thickness without any cracks
- Different patterns can be obtained
- Excellent adhesive strength
- Excellent coverage to minor substrate defects
- High permeability

• PHYSICAL SPECIFICATIONS

- | | |
|------------------------|---|
| - Specific gravity | - Approx. 1.86 g/cc |
| - Solid by weight | - Approx. 72% |
| - Coverage rate | - 0.35→0.40m ² /Kg (depending on the required texture) |
| - Dry film thickness | - Depends on the method of application and required texture |
| - Flash point | - Not applicable |
| - Finish | - Matt |
| - Drying time at 25° C | - Surface dry: approx. 2 hours Hard dry: approx. 12 hours |

• SURFACE PREPARATION

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, florescence, bond-breakers, and other contaminants.

A. OLD PAINTED SURFACES

1. Remove the old paint as much as possible.
2. Sand the entire surface and remove all the dust.
3. Wash down with Ammonia Water Solution.
4. Rinse with clean water and allow drying.
5. Prime the surface to be painted with Echo Primer Sealer.
6. Fill cracks and holes with Echo Interior putty or Echo Acrylic Filler.
7. After drying, sand the putty and clean the surface once again.
8. Apply one coat of Echo-Sintex.

B. NEW SURFACES

1. New plaster or masonry surfaces must be allowed to cure (28 days) before applying any coat.
2. Repair all cracks, holes, and other surface imperfections with a suitable patching material.
3. Sand the surface until completely smooth and remove all the dust.
4. Prime the surface to be painted with Echo primer.
5. Apply one coat of Echo-Sintex.

• INSTRUCTIONS FOR APPLICATION

- **Special trowel:**
Diluents: Clean water
Dilution ratio: 5-10% by volume

• COLOURS

- White, Standard Colors as per product's catalogue

• PACKING

- 25 kg. Pail

• STORAGE

- The product must be kept in cool well-ventilated place, protected from sunlight and heat.
- Containers must be kept tightly closed after partial usage.
- Storage life: up to 5 years from date of production, if stored as suggested.

• REMARKS

- Stir well before use.
- Avoid application below 5° C or over 85% relative humidity.
- After using, clean the application tools immediately with water.
- Keep out of children's reach.
- For more information, please do not hesitate to contact our Technical Department.