

ECHO TUNE(PATINE)

• DESCRIPTION & FIELD OF APPLICATION

Echo Tune is a high quality pure acrylic water based product with a Vinyl Acetate Copolymer. It is used for decorative effects to create beautifully finished surfaces. It is specially designed for special effect finishes as it is slow drying which allows the painter to work on a wet surface for a longer time than with normal paint to obtain a superior finish. Various patterns and designs can be obtained by using different application techniques such as marbling, sponging, rag rolling, color washing, sponging, dragging etc...

Echo Tune is recommended for use for Interior surfaces only like concrete, gypsum boards, cement, plaster and woodwork.

• MAIN FEATURES

- Easy to apply on all surface using specific tools to obtain the different decorative effects
- Long workable time
- High washability resistance (soap and water)
- Multiple Color effect
- Metal Sparkle Finish
- Environmentally friendly, lead free

• PHYSICAL SPECIFICATIONS

- | | |
|----------------------|---|
| - Color | - Semi-transparent / can be Colored |
| - Density | - 1.78+/- 0.02 gm/cc |
| - Volume Solids | - Approx. 25% |
| - Coverage Rate | - 15 - 20 m ² /Lit./ depending on effect |
| - Dry Film Thickness | - 30 Microns |
| - Flash point | - Not applicable |
| - Drying time | - Surface dry : 2 hour |
| | - Full dry : 3 hours |

• SURFACE PREPARATION

1. Surface should be stable, firm, dry; and free from laitance, dust, loose flaking materials, loose old paints, dirt, grease, wax, and any other contaminants.
2. All cracks, chips, voids, and damages should be repaired using "Echo interior putty".
3. Apply one coat of "Echo Primer Sealer".
4. Level the surface by using "Echo interior putty" and sand the surface after

- full dry.
5. Apply two coat of “Echo Super Acrylic Emulsion”, Leave minimum 2 hours between coats
 6. Using the special short pile roller, apply one or two coats of “Echo tune” and then use special application techniques like ragging, nylon stippling, and color washing, marbling, or sponging to obtain the desired effect.

- **INSTRUCTIONS FOR APPLICATION**

- **Brush, Roller, Sponge, and ragging**
 - Thinning / Cleaning of Tools : Water
 - Thinning Ratio : %10 (can be increased or decreased depending on desired pattern).

- **COLORS**

- as per product's catalogue

- **PACKING**

- 1 US gallon - 1 Kg Can

- **STORAGE**

- The product must be kept in cool well-ventilated place, protected from sunlight and heat.
- Containers must be kept tightly closed after partial usage.
- Storage life: up to 5 years from date of production, if stored as suggested.

- **REMARKS**

- Stir well before use.
- Avoid application below 5°C or over 85% relative humidity.
- After using, clean the application tools immediately with water.
- Keep out of children’s reach.
- For more information, please do not hesitate to contact our Technical Department.