

ECHO SPARKLE (STUCCO)

• **DESCRIPTION & FIELD OF APPLICATION**

Echo sparkle (Stucco) is a premium quality water based paint which provides a wonderful stucco effect for wall decorations in various attractive colors with a magical marble finish.

Echo Sparkle (Stucco) is specially designed for interior decoration and readily used on walls, plasters, concrete, gypsum board, woodboard, etc.

It is highly recommended for producing excellent marble effects on the interior walls in palaces, museums, villas, mosques, restaurant, art galleries and others.

• **MAIN FEATURES**

- Stylish and elegant
- Excellent adhesion strength
- Tintable
- Easy to apply
- Odorless, Mercury-free and Lead-free
- High durability
- Covers hairline cracks and minor blemishes on surfaces
- Wide range of patterns and finishes is achievable
- Environmentally friendly, non-toxic and non-flammable

• **PHYSICAL SPECIFICATIONS**

- | | |
|----------------------|--|
| - Color | - White or any requested color |
| - Finish | - Marble finish |
| - Density | - 1.78+/- 0.02 gm/cc |
| - Volume Solids | - Approx. 50% |
| - Coverage Rate | - 4 m ² /Ltr./ (depending on the surface) |
| - Dry Film Thickness | - 30 Microns |
| - Flash point | - Not applicable |
| - Drying time | - Surface dry : 1 hour Full dry : 3 hours |

• **SURFACE PREPARATION**

1. Surface should be stable, firm, dry, free from laitance, dust, loose flaking material and old paint, dirt, grease, wax, and any other contaminants.
2. All cracks, chips, voids and damages should be repaired using Echo interior putty.

3. Apply one coat of “Echo Primer Sealer”.
4. Level the surface by using “Echo interior putty” and sand the surface after drying.
5. Apply the first coat of “Echo sparkle Stucco” without thinning at the thickness of 0.2 mm using a putty knife, and then sand after drying.
6. Apply a second coat of “Echo sparkle Stucco” and sand after drying.
7. Apply a third coat of “Echo sparkle Stucco” according to the desired marble tile design using putty knife.
8. Remove protrusions before drying and sand it after drying fully.
9. To produce a glossy finish rub strongly over the coated surface using a putty knife to reach the desired gloss and design.
10. For a matt finish with marble appearance, follow the steps as above without rubbing using a putty knife and first coat of “Echo sparkle Stucco” Should be applied with an addition of 10% water.

- **INSTRUCTIONS FOR APPLICATION**

- **Putty Knife**
Thinning / Cleaning of Tools : Water
Thinning Ratio : %10 (can be increased or decreased depending on desired pattern).

- **COLORS**

- as per product's catalogue

- **PACKING**

- Pail / 20 Kg - 1 US gallon- 1 Kg Can

- **STORAGE**

- The product must be kept in cool well-ventilated place, protected from sunlight and heat.
- Containers must be kept tightly closed after partial usage.
- Storage life up to 5 years from date of production, if stored as suggested.

- **REMARKS**

- Stir well before use.
- Avoid application below 5° C or over 85% relative humidity.
- After using, clean the application tools immediately with water.
- For more information, please do not hesitate to contact our Technical Department.