

ECHO PRIVILEGE *(Pearl with sand effect)*

• **DESCRIPTION & FIELD OF APPLICATION**

Echo Privilege is a high quality water-based decorative paint with a metallic sand finish effect. It is designed for interior decoration. It gives a colored, pearlescent effect on walls and especially big surfaces like halls, dining rooms and flats.

Echo Privilege is recommended for use on interior surfaces and on a wide range of interior old painted surfaces such as concrete, plaster, painted walls, and glass textile.

• **MAIN FEATURES**

- Environmentally friendly
- Creates color undulations depending on light
- Creates dynamic and active environment through its changeable color structure
- Allows different color combinations to be possible at the same time
- Effaceable
- Gives an opportunity for different pattern applications

• **PHYSICAL SPECIFICATIONS**

- | | |
|----------------------|---|
| - Color | - Silver or gold (any requested color) |
| - Finish | - Colored Pearlescent metallic effect
Contains grains of sand. |
| - Density | - 1.06 to 1.30 Kg/ Ltr |
| - Volume Solids | - 36 ± 2 % |
| - Coverage Rate | - 9 m ² /Ltr / (depend on the surface) |
| - Dry Film Thickness | - 30 Microns |
| - Flash point | - Not applicable |
| - Drying time | - Surface dry : 1 hour
Full dry : 4hours |

• **SURFACE PREPARATION**

1. The surface should be stable, firm, and dry; free from laitance, dust, loose flaking material or old paints, dirt, grease, wax, and other contaminants.
2. All cracks, chips, voids, and damages should be repaired using "Echo interior putty".
3. Apply one coat of "Echo Primer Sealer".

4. Level the surface by using “Echo interior putty” and sand the surface after drying.
5. Apply two coats of “Echo Acrylic Emulsion”. Allow at least 2 hours between coats.
6. Use a special brush to paint “Echo Privilege” cross wise from corner and reverse in order to obtain the special pearlescent sand effect.

- **INSTRUCTIONS FOR APPLICATION**

- **Special brush or roller**

- Thinning / Cleaning of Tools

- : Water

- Thinning Ratio

- : %10 (can be increased or decreased depending on desired pattern).

- **COLORS**

- As per product's catalogue

- **PACKING**

- 1 US gallon - 1 Kg

- **STORAGE**

- The product must be kept in cool well-ventilated place, protected from sunlight and heat.
 - Containers must be kept tightly closed after partial usage.
 - Storage life up to 5 years from date of production, if stored as suggested.

- **REMARKS**

- Stir well before use.
 - Avoid application below 5° C or over 85% relative humidity.
 - After using, clean the application tools immediately with water.
 - Keep out of children’s reach.
 - For more information, please do not hesitate to contact our Technical Department.